

Connectable indoor units

Wall-Mounted Style



Deluxe Model		MSZ-FH06NA	MSZ-FH09NA	MSZ-FH12NA	MSZ-FH15NA	MSZ-FH18NA
Airflow (Q, L, M, H, SH)	CFM Dry	137-167-221-304-381	137-167-221-304-381	137-167-221-304-398	225-262-304-355-411	225-262-304-355-437
Sound Indoor (Q, L, M, H, SH)	Cooling dB(A)	20-23-29-36-40	20-23-29-36-40	21-24-29-36-41	27-31-35-39-44	27-31-35-39-47
Min. Ampacity	Indoor A	1				
Dimension	H in.	12-11/16	12-11/16	12-11/16	12-11/16	12-11/16
	W in.	36-7/16	36-7/16	36-7/16	36-7/16	36-7/16
	D in.	9-3/16	9-3/16	9-3/16	9-3/16	9-3/16
Pipe Size	Liq. X Gas in.	1/4 x 3/8	1/4 x 3/8	1/4 x 3/8	1/4 x 1/2	1/4 x 1/2

Model		MSZ-GL06NA*	MSZ-GL09NA	MSZ-GL12NA
Airflow (Q, L, M, H, SH)	CFM Dry	145-170-237-321-399	145-170-237-321-399	145-170-237-321-399
Sound Indoor (Q, L, M, H, SH)	Cooling dB(A)	19-22-30-37-43	19-22-30-37-43	19-22-30-37-45
Min. Ampacity	Indoor A	1		
Dimension	H in.	11-5/8	11-5/8	11-5/8
	W in.	31-7/16	31-7/16	31-7/16
	D in.	9-1/8	9-1/8	9-1/8
Pipe Size	Liq. X Gas in.	1/4 x 3/8	1/4 x 3/8	1/4 x 3/8



Model		MSZ-GL15NA	MSZ-GL18NA	MSZ-GL24NA
Airflow (Q, L, M, H, SH)	CFM Dry	205-272-335-420-533	258-332-417-522-646	388-469-544-628-738
Sound Indoor (Q, L, M, H, SH)	Cooling dB(A)	26-32-38-44-49	28-33-38-44-49	34-41-45-49-53
Min. Ampacity	Indoor A	1		
Dimension	H in.	11-5/8	12	12-13/16
	W in.	31-7/16	36-5/16	43-5/16
	D in.	9-1/8	9-13/16	9-3/8
Pipe Size	Liq. X Gas in.	1/4 x 1/2	1/4 x 1/2	3/8 x 5/8

Floor-Mounted Style

Model		MFZ-KJ09NA	MFZ-KJ12NA	MFZ-KJ15NA	MFZ-KJ18NA
Airflow (Q, L, M, H, SH)	CFM Dry	138-173-208-251-275	138-173-208-251-275	198-237-282-328-374	198-237-282-328-374
Sound Indoor (Q, L, M, H, SH)	Cooling dB(A)	21-25-30-34-38	21-25-30-34-38	28-31-36-40-43	28-31-36-40-43
Min. Ampacity	Indoor A	1			
Dimension	H in.	23-5/8	23-5/8	23-5/8	23-5/8
	W in.	29-17/32	29-17/32	29-17/32	29-17/32
	D in.	8-15/32	8-15/32	8-15/32	8-15/32
Pipe Size	Liq. X Gas in.	1/4 x 3/8	1/4 x 3/8	1/4 x 1/2	1/4 x 1/2



Connectable indoor units

1-Way Cassette Style

Model			MLZ-KP09NA	MLZ-KP12NA	MLZ-KP18NA
Airflow (Q, L, M, H, SH)	CFM Dry		212-254-282-311	212-258-297-332	212-293-346-403
Sound Indoor (Q, L, M, H, SH)	Cooling	dB(A)	27-31-34-38	27-32-36-40	29-36-41-47
Min. Ampacity	Indoor	A	1		
Dimension	H	in.	7-5/16	7-5/16	7-5/16
	W	in.	43-3/8	43-3/8	43-3/8
	D	in.	14-3/16	14-3/16	14-3/16
Pipe Size	Liq. X Gas	in.	1/4 x 3/8	1/4 x 3/8	1/4 x 1/2



4-Way Cassette Style

Model			SLZ-KF09NA	SLZ-KF12NA	SLZ-KF15NA
Airflow (L,M, H)	CFM Dry		230-265-300	230-280-335	245-315-405
Sound Indoor (L, M, H)	Cooling	dB(A)	25-28-31	25-30-34	27-34-39
Min. Ampacity	Indoor	A	.25	.3	.4
Dimension	H	in.	8-3/16	8-3/16	8-3/16
	W	in.	22-7/16	22-7/16	22-7/16
	D	in.	22-7/16	22-7/16	22-7/16
Pipe Size	Liq. X Gas	in.	1/4 x 3/8	1/4 x 3/8	1/4 x 1/2



Multi-Position Air Handler

Low Static Pressure (0.8" WG) Model			SVZ-KP12NA	SVZ-KP18NA	SVZ-KP24NA
Airflow (L,M, H)	CFM Dry		278-381-448	471-573-675	515-625-735
Sound Indoor (L, M, H)	Cooling	dB(A)	29-36-39	33-36-41	
Min. Ampacity	Indoor	A	3		
Dimension	H	in.	39-13/16	39-13/16	39-13/16
	W	in.	17	17	17
	D	in.	21-5/8	21-5/8	21-5/8
Pipe Size	Liq. X Gas	in.	1/4 x 3/8	1/4 x 1/2	3/8 x 5/8
External Static Pressure		in. WG	0.3 - 0.5 - 0.8		

Low Static Pressure (0.8" WG) Model			SVZ-KP30NA	SVZ-KP36NA
Airflow (L,M, H)	CFM Dry		613-744-875	767-910-910
Sound Indoor (L, M, H)	Cooling	dB(A)	32-37-41	35-40-42
Min. Ampacity	Indoor	A	4.13	
Dimension	H	in.	43-3/4	43-3/4
	W	in.	21	21
	D	in.	21-5/8	21-5/8
Pipe Size	Liq. X Gas	in.	3/8 x 5/8	
External Static Pressure		in. WG	0.3 - 0.5 - 0.8	

